

B PLUS SPECIAL APPLICATION (CLASS B)

Using the wrong extinguisher on the wrong class of fire can have fatal consequences. A water extinguisher used to put out an electrical fire, for instance, only helps spread the fire, and poses the added threat of electrocution. So what do you do when you don't know what kind of fire you are fighting? You go for B+.

Ceasefire's B+ is so potent, it packs in all the force of a 16 kg extinguisher into a 4 kg body. That's 4 times the power! That's what makes it the perfect extinguisher choice for petrol pumps and petrochemical units. The Ceasefire B+ is ideal for Class B & C fires, involving petrol, alcohol, industrial chemicals and more. The reason for this is its unique powder which splits into four upon activation, covering a huge surface area.



| FIGHTS CLASS | CERTIFICATIONS | CERTIFYING BODY |
|--------------|----------------------------|-----------------|
| B C | EN3-7 & 8 CE 112E ISO 9001 | LPCB UKAS 9001 |

SIZES AVAILABLE:

| PRODUCT CODES | | | | |
|---------------|-----------|-----------|-----------|-----------|
| VARIANT | 2 KG | 4 KG | 6 KG | 9 KG |
| B PLUS | CF-000736 | CF-000737 | CF-000738 | CF-000739 |

FEATURES:

| | | |
|--|--|--|
| | Easy snap safety seal | |
| | State-of-the-art pressure gauge | |
| | Controllable discharge mechanism | |
| | Works on Class B and C fires | |
| | Deep drawn & CO2 MIG welded can construction | |
| | Forging and machining valve construction | |
| | Epoxy polyester powder external coating | |
| | Epoxy powder internal coating | |



TECHNICAL SPECIFICATIONS:

| Technical Specifications | 2 kg Powder - B+ | 4 kg Powder - B+ | 6 kg Powder - B+ | 9 kg Powder - B+ |
|----------------------------|------------------|-------------------|-------------------|-------------------|
| Agent | BC Powder | BC Powder | BC Powder | BC Powder |
| Gross Weight (kg) | 4.90 | 7.50 | 11.60 | 15.30 |
| Empty Weight (kg) | 2.90 | 3.50 | 5.60 | 6.30 |
| Can Height (mm) | 440 | 485 | 620 | 620 |
| Diameter (mm) | 140 | 160 | 175 | 204 |
| Minimum Discharge Time (s) | 9 | 15 | 15 | 15 |
| Discharge Mechanism | Lever | Squeeze Grip Type | Squeeze Grip Type | Squeeze Grip Type |
| Minimum Range (m) | 2 | 2 | 2 | 2 |
| Ratings (B) | 89 | 233 | 233 | 233 |
| Sheet Metal Thickness (mm) | 1.6 | 1.6 | 2 | 2 |
| Certification Standard | Yes | Yes | Yes | Yes |
| Certification Standard | EN-3 | EN-3 | EN-3 | EN-3 |

* Please check specification before ordering. Specification can change without notice due to continuous R & D.

APPLICATION AREAS:



Garment Stores and Warehouses



Hospitals



Hotels



Schools



Restaurants and Food Supply Chain



Heritage Buildings