

FOAM BASED PORTABLE EXTINGUISHER

Basic science proves fire needs oxygen to grow. Without oxygen, even the largest fires will die out in minutes.

Ceasefire's Foam-based Extinguishers exploit this weakness by creating a chemical foam that blankets the flames and cuts off the oxygen supply. Its squeeze grip mechanism makes it faster and easier to use. The proprietary stored pressure technology also delivers high power

throw, making these extinguishers extremely effective. While they are effective against Class A and B fires, they are ideal for use on burning liquids like oil and petrol.



FIGHTS CLASS

A B

CERTIFICATIONS

EN3-7 & 8



CERTIFYING BODY












SIZES AVAILABLE:

SS: Stainless Steel | MS: Mild Steel



PRODUCT CODES								
VARIANT	3 LTR SS	3 LTR MS SP	6 LTR SS SP	6 LTR SS CHROME	6 LTR MS SP	9 LTR SS SP	9 LTR SS CHROME	9 LTR MS SP
FOAM	CF-000779	CF-000805	CF-000715	CF-000986	CF-000806	CF-000716	CF-000987	CF-000807

FEATURES:

	Easy snap safety seal	
	State-of-the-art pressure gauge	
	Controllable discharge mechanism	
	Works on Class A and B fires	
	Seamed MIG welded can construction	
	SS forged ball valve construction	
	Epoxy polyester powder external coating	
	Epoxy powder internal coating (only on MS type)	



TECHNICAL SPECIFICATIONS:

Technical Specifications		3 ltr Foam (SS)	3 ltr Foam (MS)	6 ltr Foam (SS)	6 ltr Foam (SS) Chrome Finish	6 ltr Foam (MS)	9 ltr Foam (SS)	9 ltr Foam (SS) Chrome Finish	9 ltr Foam (MS)
Agent		AFFF FOAM	AFFF FOAM	AFFF FOAM	AFFF FOAM	AFFF FOAM	AFFF FOAM	AFFF FOAM	AFFF FOAM
Gross Weight (kg)		5.7	5.72	9.6	9.6	9.68	13.4	13.4	14.4
Empty Weight (kg)		2.7	2.72	3.6	3.6	3.8	4.4	4.4	5.4
Can Height (mm)		430	440	515	515	520	610	610	620
Diameter (mm)		140	140	160	160	160	175	175	175
Minimum Discharge Time (s)		9	9	15	15	15	15	15	15
Discharge Mechanism		Squeeze Grip	Squeeze Grip	Squeeze Grip	Squeeze Grip	Squeeze Grip	Squeeze Grip	Squeeze Grip	Squeeze Grip
Minimum Range (m)		2	2	2	2	2	2	2	2
Ratings	(A)	8	8	13	13	13	21	21	21
	(B)	89	89	144	144	144	233	233	233
Sheet Metal Thickness (mm)		1.5	1.6	1.5	1.5	1.6	1.5	1.5	2
Testing Helium Leak		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Certification Standard		EN-3	EN-3	EN-3	EN-3	EN-3	EN-3	EN-3	EN-3t

* Please check specification before ordering. Specification can change without notice due to continuous R & D.

APPLICATION AREAS:



Garment Stores and Warehouses



Hospitals



Hotels



Schools