

## WATER BASED TROLLEY MOUNTED EXTINGUISHER



FIGHTS CLASS

**A**

CERTIFICATIONS

**EN-1866**



CERTIFYING BODY



**SIZES AVAILABLE:**

SS: Stainless Steel | MS: Mild Steel

PRODUCT CODES								
VARIANT	50 LTR SS	50 LTR MS	50 LTR SS	50 LTR MS	100 LTR SS	100 LTR MS	100 LTR SS	100 LTR MS
WATER	CF-000755	CF-001031	CF-000756	CF-001032	CF-000886	CF-001033	CF-000973	CF-001034

**FEATURES:**

	EPDM rubber hosepipe	
	Easy snap safety seal	
	State-of-the-art pressure gauge	
	Controllable discharge mechanism	
	Works on Class A fire	
	Seamed MIG welded can construction	
	Forging and machining valve construction	
	Epoxy polyester powder external coating	
	Epoxy powder internal coating (only on MS type)	



TECHNICAL SPECIFICATIONS:

Technical Specifications	50 ltr Water Stored Pressure (SS)	50 ltr Water Stored Pressure (MS)	50 ltr Water Spot Pressure (SS)	50 ltr Water Spot Pressure (MS)	100 ltr Water Stored Pressure (SS)	100 ltr Water Stored Pressure (MS)	135 ltr Water Stored Pressure (SS)	135 ltr Water Stored Pressure (MS)
Agent	Water	Water	Water	Water	Water	Water	Water	Water
Gross Weight (kg)	105.8	115.7	104.6	112.6	166.9	181.5	203.9	219
Empty Weight (kg)	55.8	65.7	54.6	62.5	66.9	81.5	68.9	84
Can Height (mm)	1490	1520	1230	1230	1530	1510	1590	1570
Diameter (mm)	300	300	300	300	400	400	450	450
Minimum Discharge Time (s)	40	40	40	40	80	80	120	120
Discharge Mechanism	Controllable	Controllable	Controllable	Controllable	Controllable	Controllable	Controllable	Controllable
Minimum Range (m)	6	6	6	6	6	6	6	6
Ratings (A)	21	21	21	21	21	21	21	21
Sheet Metal Thickness (mm)	2	3	2	3	2.5	3.5	3	3.5
Certification Standard	EN-1866	EN-1866	EN-1866	EN-1866	EN-1866	EN-1866	EN-1866	EN-1866

\* Please check specification before ordering. Specification can change without notice due to continuous R & D.

APPLICATION AREAS:



Warehouses



Furniture store



Transportation factories



Dry fruit stores



Grocery shops



PVC plastic industries



Tyre Factories



Godowns